

DENON

Hi-Fi AM-FM Stereo Receiver


For EUROPEAN
And U.K. Models

SERVICE MANUAL


MODEL DRA-565RD

MODEL DRA-365RD

AM-FM STEREO RECEIVER



DRA-565RD




DRA-365RD



TABLE OF CONTENTS

OPERATING INSTRUCTIONS	2-9
DISASSEMBLY	10, 11
METHOD OF ADJUSTMENTS	12
CONNECTION DIAGRAM OF MEASURING INSTRUMENTS	13
SEMICONDUCTORS	13-16
BLOCK/LEVEL DIAGRAM (DRA-565RD)	17
BLOCK/LEVEL DIAGRAM (DRA-365RD)	17
NOTE ON PARTS LIST	18
PRINTED WIRING BOARD PARTS LIST (DRA-565RD)	18, 19
PRINTED WIRING BOARD PARTS LIST (DRA-365RD)	19, 20
PRINTED WIRING BOARD PATTERNS	21-23
1U-2731B MAIN UNIT (DRA-565RD)	21
1U-2731 MAIN UNIT (DRA-365RD)	22
1U-2732B TUNER & DISPLAY UNIT (DRA-565RD)	23
1U-2732 TUNE & DISPLAY UNIT (DRA-365RD)	24
WIRING DIAGRAM	25
EXPLODED VIEW OF CHASSIS AND CABINET (DRA-565RD)	26
PARTS LIST OF EXPLODED VIEW (DRA-565RD)	27
PARTS LIST OF EXPLODED VIEW (DRA-365RD)	28
EXPLODED VIEW OF CHASSIS AND CABINET (DRA-365RD)	29
SCHEMATIC DIAGRAM (for DRA-565RD)	31
SCHEMATIC DIAGRAM (for DRA-365RD)	32


NIPPON COLUMBIA CO., LTD.





CAUTION

RISK OF ELECTRIC SHOCK

DO NOT OPEN



CAUTION: TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK). NO USER SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.

The lightning flash with arrowhead symbol, within an equilateral triangle, is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.

The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

WARNING: TO REDUCE THE RISK OF FIRE OR ELECTRIC SHOCK, DO NOT EXPOSE THIS APPLIANCE TO RAIN OR MOISTURE.

Konformitätsbescheinigung

Die DENON Electronic GmbH
Halskestraße 32
40880 Ratingen

Erklärt als Hersteller/Importeur, daß das in dieser Bedienungsanleitung beschriebene Gerät den Technischen Vorschriften für Ton- und Fernseh-Rundfunkempfänger nach der Amtsblattverfügung 808/1992 (Amtsblatt des Bundesministers für Post und Telekommunikation vom 31. 8. 1992) entspricht.

PRECAUTIONS FOR INSTALLATION

Install DRA-565/365RD always horizontally. And leave at least 10 cm of space between this unit and other component placed above.

VORKEHRUNGEN FÜR DIE AUFSTELLUNG

Der DRA-565/365RD ist stets waagrecht aufzustellen. Außerdem muß ein Mindestabstand von 10 cm zwischen diesem Gerät und der Komponente gewährleistet werden, die darüber gestellt wird.

PRECAUTIONS D'INSTALLATION

Le DRA-565/365RD doit toujours être installé horizontalement. Et laisser au moins un espace de 10 cm entre cet appareil et l'autre composant placé au-dessus.

PRECAUZIONI PER L'INSTALLAZIONE

Il DRA-565/365RD viene sempre installato in modo orizzontale. Lasciate uno spazio di almeno 10 cm tra quest'unità e un eventuale componente sovrapposto.

PRECAUCIONES PARA LA INSTALACION

Instale siempre el DRA-565/365RD en posición horizontal. Asegúrese también de dejar un espacio de por lo menos 10 cm entre esta unidad y el componente que sea colocado encima.

VOORZORGSMAATREGELEN VOOR INSTALLATIE


De DRA-565/365RD altijd horizontaal plaatsen. En minstens 10 cm ruimte laten tussen dit toestel en het andere component dat u erboven plaatst.

FÖRBEREDELSE FÖR INSTALLATION



Installera alltid DRA-565/365RD horisontellt. Lämna åtminstone 10 cm mellan denna apparat och en annan komponent som placeras ovanpå.

PRECAUÇÕES PARA A INSTALAÇÃO


Instale sempre horizontalmente o DRA-565/365RD. E deixe pelo menos 10 cm de espaço entre esta unidade e o outro componente colocado acima.




NOTE ON USE/HINWEISE ZUM GEBRAUCH/OBSERVATIONS RELATIVES A L'UTILISATION
NOTE SULL'USO/NOTAS SOBRE EL USO/ALVORENS TE GEBRUIKEN/OBSERVERA
OBSERVAÇÕES QUANTO AO USO

 <ul style="list-style-type: none"> • Avoid high temperatures. Allow for sufficient heat dispersion when installed on a rack. • Vermeiden Sie hohe Temperaturen. Beachten Sie, daß eine ausreichende Luftzirkulation gewährleistet wird, wenn das Gerät auf ein Regal gestellt wird. • Éviter des températures élevées. Tenir compte d'une dispersion de chaleur suffisante lors de l'installation sur une étagère. • Evitare di esporre l'unità a temperature alte. • Assicurarsi che ci sia un'adeguata dispersione del calore quando si installa l'unità in un mobile per componenti audio. • Evite altas temperaturas. Permita la suficiente dispersión del calor cuando está instalado en la consola. • Vermied hohe temperaturen. Zorg voor een deeglijk hitteafvoer indien het apparaat op een rek wordt geplaatst. • Undvik höga temperaturer. Se på at der findes tilstrækkelig til god varmeafledning ved monteringen i en rack. • Evite temperaturas altas. Garanta suficiente dispersão de calor quando o equipamento for instalado numa prateleira. 	 <ul style="list-style-type: none"> • Keep the set free from moisture, water, and dust. • Halten Sie das Gerät von Feuchtigkeit, Wasser und Staub fern. • Protéger l'appareil contre l'humidité, l'eau et la poussière. • Tenere l'unità lontana dall'umidità, dall'acqua e dalla polvere. • Mantenga el equipo libre de humedad, agua y polvo. • Laat geen vochtigheid, water of stof in het apparaat binnenvallen. • Utsett ikke apparaten for fukt, vann eller støv. • Mantenha o aparelho livre de qualquer umidade, água ou poeira. 	 <ul style="list-style-type: none"> • Do not let foreign objects in the set. • Keine fremden Gegenstände in das Gerät kommen lassen. • Ne pas laisser des objets étrangers dans l'appareil. • È importante che nessun oggetto sia inserito all'interno dell'unità. • No deve objetos estranhos dentro del equipo. • Laat geen vreemde voorwerpen in de apparaten vallen. • Se ill et fremmede föremål inne i apparaten. • Não deixe objetos estranhos no aparelho.
 <ul style="list-style-type: none"> • Handle the power cord carefully. Hold the plug when unplugging the cord. • Gehen Sie vorsichtig mit dem Netzkabel um. Halten Sie das Kabel am Stecker, wenn Sie den Stecker herausziehen. • Manipuler le cordon d'alimentation avec précaution. Tenir la prise lors du débranchement du cordon. • Maneggiare il filo di alimentazione con cura. Agire per la spina quando scollegare il cavo dalla presa. • Manège el cordón de energía con cuidado. Sostenga el enchufe cuando desconecte el cordón de energía. • Hanteret het netkabel voorzichtig. Houd het snoer bij de stecker vast wanneer deze moet worden aan- of losgeplaatst. • Hanterer netkabeln varsamt. Håll i kablens nål den kopplet från el uttaget. • Manuseie com cuidado o fio condutor de energia. Segure a tomada ao desconectar o fio. 	 <ul style="list-style-type: none"> • Unplug the power cord when not using the set for long periods of time. • Wenn das Gerät eine längere Zeit nicht verwendet werden soll, trennen Sie das Netzkabel vom Netzstecker. • Débrancher le cordon d'alimentation lorsque l'appareil n'est pas utilisé pendant de longues périodes. • Disinnestare il filo di alimentazione quando avete l'intenzione di non usare il filo di alimentazione per un lungo periodo di tempo. • Desconecte el cordón de energía cuando no utilice el equipo por mucho tiempo. • Neem altijd het netkabel uit het stopcontact wanneer het apparaat gedurende een lange periode niet wordt gebruikt. • Røpplis ut nettkabelen om apparaten inte kommer til anbringes i lang tid. • Desligue o fio condutor de força quando o aparelho não tiver que ser usado por um longo período. 	 <ul style="list-style-type: none"> • Never disassemble or modify the set in any way. • Vorziehen Sie niemals das Gerät auseinander zu nehmen oder auf jegliche Art zu verändern. • Ne jamais démonter ou modifier l'appareil d'une manière ou d'une autre. • Non smontare mai, né modificare l'unità in nessun modo. • Nunca desarme o modifique el equipo de ninguna manera. • Noet de apparaten demonteren of op andere wijze modificeren. • Te me iðr apparaten och forset into byrgja ein den. • Nunca desmonte ou modifique o aparelho de alguma forma.

FRONT PANEL



REAR PANEL



Please check the following items are included with the main unit in the carton:

- | | |
|----------------------------------|---|
| (1) Operating Instructions | 1 |
| (2) AM Loop Antenna | 1 |
| (3) FM Antenna | 1 |
| (4) Remote Control RC-174 | 1 |
| (5) Batteries R6 (AA) | 2 |

Bitte überprüfen Sie, ob die folgenden Teile vollständig in der Verpackung enthalten sind:

- | | |
|---|---|
| (1) Bedienungsanleitung | 1 |
| (2) AM-Rahmenantenne | 1 |
| (3) UKW-Antenne | 1 |
| (4) Fernbedienungsgerät RC-174 | 1 |
| (5) Trockenzelle-Batterie R6 (AA) | 2 |

Veuillez contrôler que les articles suivants sont bien joints à l'appareil principal dans le carton:

- | | |
|-----------------------------------|---|
| (1) Mode d'emploi | 1 |
| (2) Antenne-cadre AM | 1 |
| (3) Antenne FM | 1 |
| (4) Télécommande RC-174 | 1 |
| (5) Piles de format R6 (AA) | 2 |

Controllare che le parti seguenti si trovino imballate con l'apparecchio nella scatola di spedizione.

- | | |
|------------------------------------|---|
| (1) Istruzioni per l'uso | 1 |
| (2) Antenna AM a telaio | 1 |
| (3) Antenna FM | 1 |
| (4) Telecomando RC-174 | 1 |
| (5) Batterie a secco R6 (AA) | 2 |

Por favor verifique que los siguientes artículos son empacados en la caja pero separados de la unidad principal.

- | | |
|---|---|
| (1) Instrucciones de operación | 1 |
| (2) Antena AM de cuadro | 1 |
| (3) Antena de FM | 1 |
| (4) Unidad de control remoto RC-174 | 1 |
| (5) Pilas secas R6 (AA) | 2 |

Kontroleer of de volgende accessoires bij het hoofdtoestel in de doos zijn verpakt:

- | | |
|--------------------------------------|---|
| (1) Gebruiksaanwijzing | 1 |
| (2) AM-raamantenne | 1 |
| (3) FM-antenne | 1 |
| (4) Afstandsbediening RC-174 | 1 |
| (5) R6 (AA) droge cel batterij | 2 |

Kontrollera att följande tillbehör har packats ner i kartongen tillsammans med huvudenheten.


- | | |
|---------------------------------|---|
| (1) Bruksanvisning | 1 |
| (2) Ramantenn för AM-bruk | 1 |
| (3) FM-antenn | 1 |
| (4) Fjärrkontroll RC-174 | 1 |
| (5) R6 (AA) torrbatteri | 2 |

Confirme-se de que as seguintes peças estão incluídas na embalagem fora da unidade principal:

- | | |
|----------------------------------|---|
| (1) Instruções de operação | 1 |
| (2) Antena de quadro AM | 1 |
| (3) Antena FM | 1 |
| (4) Controle remoto RC-174 | 1 |
| (5) Pilhas R6 (AA) | 2 |

For multi-voltage models only:

- The desired voltage may be set with the VOLTAGE SELECTOR KNOB on the rear panel, using a screwdriver.
- Do not twist the VOLTAGE SELECTOR KNOB with excessive force as this may cause damage.
- If the VOLTAGE SELECTOR KNOB does not turn smoothly, please contact a qualified serviceman.



(The voltage is set to 220 V upon shipment from the factory.)

- FREQUENCY STEP (Frequency step switch)**
Set the FREQUENCY STEP switch as described below.
- In the U.S.A. and Canada - set the switch to 100 kHz / 10 kHz side.
With this setting, the frequency varies in 100 kHz steps in the range of 87.5 to 108.0 MHz (FM) and in 10 kHz steps in 520 to 1710 kHz (AM).
 - Elsewhere - set the switch to 50 kHz / 5 kHz side.
With this setting, the frequency varies in 50 kHz steps in the range of 87.50 to 108.0 MHz (FM) and in 5 kHz steps in 522 to 1611 kHz (AM).

DESIGNATIONS AND FUNCTIONS OF PANEL CONTROLS (Refer to Page 5.)

FRONT PANEL

- 1 **POWER (Power ON-STANDBY/OFF Switch)**
This switch turns the unit ON or OFF. There is a delay of approximately 3 seconds before the unit will operate after this power switch is turned ON. If the unit is turned OFF from the remote control, the unit will be in the STANDBY mode. When in the STANDBY mode, the unit can be turned ON with the power button on the remote control. If the unit will not be used for extended period, be sure to turn the unit OFF from the front panel power switch.
NOTE: This unit includes a STANDBY protection feature. This feature is designed to prevent accidental turn-on from the STANDBY mode in the event of a power failure. Should AC power be disconnected and then reconnected when the unit is in STANDBY mode, the unit will return to the STANDBY mode.
To turn the unit ON from the STANDBY mode without the remote control, operate the front panel power switch four times. The unit will then operate normally.
- 2 **PHONES (Headphones Jack)**
Connect a pair of headphones (sold separately) to this jack for private listening.
- 3 **SPEAKERS (Speaker selector switches)**
These switches are used to select speaker system A and B. No sound is heard through the speakers when both switches are reset to the (A) position.
- 4 **REMOTE SENSOR (Remote control sensor)**
This sensor receives the infra-red light transmitted from the wireless remote control unit.
For remote control, point the wireless remote control unit towards the sensor.
- 5 **BASS (Bass control)**
Use this control to adjust the low-range response. When the control is set to the center position, the frequency characteristic curve (below 1,000 Hz) is flat. Turn the control clockwise to increase the bass response and counter-clockwise to decrease it.
- 6 **TREBLE (Treble control)**
Use this control to adjust the high-range response. When the control is set to the center position, the frequency characteristic curve (above 1,000 Hz) is flat. Turn the control clockwise to increase the treble response and counter-clockwise to decrease it.
- 7 **BALANCE (Balance control)**
Use this control to balance the volume levels between left and right channels. The volume levels in both channels are equal when the control is set to the center position.
- 8 **VARIABLE LOUDNESS (Loudness control)**
At low volumes, the human ear is less sensitive to low (BASS) and high (TREBLE) frequencies. Use this control to compensate for this deficiency when listening at low volume levels. Turn this control counter-clockwise until a natural balance of bass and treble sound has been restored.
- 9 **BASS EQ (DRA-565RD only)**
Press this button to switch the BASS EQ ON () for emphasis of bass sounds.
Use in conjunction with the bass adjustment of the tone control will provide further emphasis of bass sounds. Set this switch to OFF () when you wish to listen with a normal setting condition.
- 10 **VOLUME (Volume control)**
This knob is used to adjust the volume level of both channels.
Turn the knob clockwise to raise the volume and counter-clockwise to lower it.

- 11 **Input selector (Input selector buttons)**
These buttons are used to select the audio input source.
 - PHONO: Press to play a record on a record player connected to the PHONO input jacks.
 - CD: Press to listen to a compact disc player or another component connected to the CD input jacks.
 - TUNER: Press to listen to FM or AM programs.
 - VIDEO: Use when playing back the audio from a Hi-Fi video, video disc player or other component connected to the VIDEO terminal.
- 12 **Tape selector (Tape selector/monitor buttons) (DRA-565RD)**
TAPE-1: Press this button once, TAPE-1 indicator will light up and then you can play tape source on TAPE-1 terminal.
In this state you can copy TAPE-1 source to TAPE-2 terminal.
TAPE-2: Press this button once, TAPE-2 indicator will light up and then you can play tape or video source of TAPE-2 terminal.
Press again the button currently accessed, to play sources selected by input selector 11, indicator goes out.
• TAPE (Tape monitor button) (DRA-365RD)
Press this button once, TAPE indicator will light up and then you can play tape source on the TAPE terminal. Press again the button currently accessed, to play sources selected by input selector 11, indicator goes out.
- 13 **RDS button**
This button is used for the RDS search (refer to page 12) and PTY search (refer to page 12), and TP search (refer to page 12) operations, and to input the station name (refer to page 12, 13).
- 14 **BAND (Band selector switch)**
Press this switch to select the FM or AM (MW) band.
- 15 **AUTO (Tuning mode button)**
This switches between auto and manual tuning.
Auto tuning: When the UP button is pressed, the radio is tuned automatically to a higher frequency. Press the DOWN button to tune to a lower frequency. Use this position to eliminate noise when no signals or weak signals are being received.
Manual tuning: In this position, the radio can be tuned manually. Reception is automatically monaural when in the manual mode.
- 16 **TUNING (Tuning buttons)**
Use these to change the received frequency to a higher frequency (UP) or a lower frequency (DOWN).
When writing station names, use these buttons to select the letters. (Refer to Page 13.)
- 17 **MEMORY (Memory button)**
This switch is used to store the desired radio station to a memory.
 - Presetting stations
After pressing the MEMORY button, press the SHIFT/PTY button to select the memory block, A to E. Now use the PRESET UP and DOWN buttons to specify the preset channel number. Press the MEMORY button again to store the station at the specified preset channel.

- 18 **Preset (Preset station buttons)**
These buttons are used for storing stations or recalling stations which have been preset. Using the SHIFT button you can preset a total of 40 FM or AM stations into preset channels.
Once a radio has been memorized, the same station can later be tuned in instantly simply by recalling the corresponding preset channel with PRESET UP or DOWN button.

DISPLAY

- 19 **RDS Indicator**
This lights when receiving RDS broadcasts, and flashes during the RDS search operations.
- 20 **TA Indicator**
This lights when receiving traffic announcements.
- 21 **TP Indicator**
This flashes during the TP search operation and lights when TP stations are tuned in.
- 22 **PTY Indicator**
This flashes during the PTY (Programme type) search operation.
- 23 **TUNED Indicator**
This lights when a station is properly tuned in.
- 24 **STEREO Indicator**
This lights when receiving stereo broadcasts. It remains off when receiving AM broadcasts.
- 25 **AUTO Indicator**
This indicates the tuning mode. It lights in the auto mode, and remains off in the manual mode.
NOTE:
 - TP (Traffic Programme)
 - Stations scheduled to broadcast traffic programmes
 - TA (Traffic Announcement)
 - Traffic information broadcasts
- 26 **MEMO indicator**
This indicator lights for approximately 10 seconds when the MEMORY button has been pressed and a station can be stored on a PRESET CHANNEL button.
This flashes continuously during the auto memory operation.
- 27 **CH indicator**
This lights when the preset channel number and shift mode (A, B, C, D or E) are displayed.
- 28 **TAPE-1/TAPE-2 indicator (DRA-565RD)**
The TAPE-1 indicator lights when the TAPE-1 source is selected with the tape selector buttons. The TAPE-2 indicator lights when the TAPE-2 source is selected.
- 29 **TAPE indicator (DRA-365RD)**
The TAPE indicator lights when the TAPE source is selected with the tape selector buttons.
- 30 **Multi function display**
This displays the frequency, station name, programme type, etc.

REAR PANEL


- 1 **FM ANT (FM antenna terminals)**
75-ohm coaxial cable can be connected to this terminal. For antenna connecting procedure, see the ANTENNA INSTALLATION.
- 2 **GND (Grounding terminal)**
The grounding wire of the turntable is connected here.
 - Hum or noise may be generated if the grounding wire is not connected.
- 3 **AM ANT (AM antenna terminals)**
Connect the attached AM loop antenna. (Refer to page 10 for connections).
Connect to this terminal when a medium wave outdoor antenna is used.
- 4 **PHONO (Phono input terminals)**
The output cord of the turntable is connected here.
Since the input sensitivity of "PHONO" is extremely high, do not use the unit without the input pin cord. If used without this cord, the speakers may generate hum.
- 5 **CD**
The output cord of the CD player is connected here.
- 6 **VIDEO**
A VIDEO, such as a VCR or Video Disc may be connected here.
- 7 **TAPE-1, TAPE-2 (Tape deck playback/recording terminal) (DRA-565RD)**
Two tape decks or tape deck can be connected to these jacks for full-fledged playback, recording and tape dubbing operation.
- 8 **TAPE (DRA-365RD)**
Tape decks can be connected for full use including playing or copying.
- 9 **PRE-OUT (DRA-565RD only)**
Output signals for power amplifiers are sent from these jacks.
The rated output is 2 volts.
- 10 **SPEAKER SYSTEMS (Speaker terminals)**
Two pairs of speakers A and B can be connected to these terminals.
- 11 **AC OUTLET (AC power outlets)**
This AC outlet is controlled by the power switch and Remote control unit (DRA-565RD), controlled by the power switch (DRA-365RD).
- 12 **AC CORD (Power cord)**
Connect this cord into the wall outlet.

NOTES

- This receiver has a full back-up system. When the power is turned on, the INPUT SELECTOR buttons are set to the last mode set before the power was turned off.
- When using this receiver in close proximity to video equipment (TV, VCR, VDP, etc.), noise may be generated in AM broadcasts. To


avoid this, keep the receiver as far away from other video components as possible, or place the AM loop antenna where noise is reduced. If the noise is not reduced, turn off the power of the video components when listening to AM broadcasts.

CONNECTIONS



ANTENNA INSTALLATION

- FM ANTENNA**
The supplied indoor FM antenna can be used inside wooden houses for receiving local FM stations and other strong FM signals. Stretch out the ends of the antenna and mount the antenna on the wall or ceiling where optimum reception is achieved. A indoor FM antenna may not consistently ensure stable reception, due to environment changes. In such cases, the indoor FM antenna should only be used temporarily until an outdoor FM antenna has been installed.
When connecting an outdoor FM antenna, the use of 75 ohm coaxial cable (3C-2V, 5C-2V) is strongly recommended.
- AM ANTENNA**
Attach the supplied AM loop antenna even when using an outdoor AM antenna.
Connect the leads to the AM and GND terminals.
Also use the AM terminals for connecting an outdoor AM antenna (when making such a connection do not disconnect the AM loop antenna.)
Adjust the loop antenna to obtain optimum reception. Where broadcast stations are distant and only weak signals are received, or where signals are blocked, it is best to install an outdoor AM antenna.



SPEAKER CONNECTION

Confirm polarity (+, -) and left and right channels (L, R). Connect the speaker pairs to the SPEAKER terminals A or B on the back panel. Connections must be made with power cord disconnected.

Preparing the cord

1. Peel off the sheath.



2. Twist the wires.



Connecting the front speaker terminals

1. Loosen by turning counterclockwise.



2. Insert the cord and tighten by turning clockwise.



Notes on Connection

- Do not plug the power cord into the AC wall outlet until all connections have been completed.
- Make sure channels are correctly connected. Connect Left channels to Left channels and Right channels to Right channels. Follow the color markings of plugs and terminals to make sure mistakes are not made.
- Connect all pin-plugs securely, pushing them completely into the jacks. Incomplete connections will cause noise generation.
- Binding the connection cables to power cords, or running such cables close to power supply transformers will cause humming or noise, and should thus be avoided.

Notes:

- Do not connect two FM antennas simultaneously.
- Even if an external AM antenna is used, do not disconnect the AM loop antenna.
- Make sure AM loop antenna lead terminals do not touch metal parts of the panel.

CAUTION

Protective Circuit

This set is equipped with a high speed protective circuit. This circuit protects the internal circuitry from damage due to large currents flowing when the speaker jacks are not completely connected or when an output is generated by a short circuit.
This protective circuit's operation cuts off the output to the speakers. In such a case, be sure to turn the power to the set off and check the connections to the speakers. Then turn the power on again. After muting for several seconds, the set will operate normally.

Using the Various Functions

1. Presetting stations in the memory

The frequency and the name of the radio station (including names which you have input yourself), are also stored in the memory. In particular, the various RDS functions can be used effectively when RDS stations are stored in the memory.

How to preset the memory

Press the MEMORY button **M**. The "MEMO" indicator on the display **M** lights. Next, use SHIFT/PTY button **S** to select the memory block A, B, C, D or E. Now press the PRESET UP or DOWN button **P** to specify the preset channel number, and then press the MEMORY button **M** to store the station in the memory.

The preset channel numbers for the different memory blocks are as follows.

Memory block A	: 1 to 8
Memory block B	: 1 to 8
Memory block C	: 1 to 8
Memory block D	: 1 to 8
Memory block E	: 1 to 8

2. Auto Memory (FM only)

The DRA-565RD/DRA-365RD is equipped with an auto memory function. Connected the antenna, set it so that stations can be received, then hold in the MEMORY button and press the POWER button to turn the power on. Stations for which the auto stop function operates are stored in the preset memory in the order A1 to A8, B1 to B8, and so on, through E8. Channel A1 is tuned in after the auto memory operation is completed.

Using this function makes it possible to find out the overall reception conditions of the receivable stations. The memory can be used effectively by recalling the channels in the preset memory and replacing stations whose reception is poor with stations whose reception is good, using the procedure described in 1 above.

3. Recalling preset stations

Use the SHIFT/PTY button **S** to select memory block A, B, C, D or E, then press the PRESET UP or DOWN button **P** to recall the station stored in the memory. If the PRESET UP or DOWN buttons are pressed without pressing the SHIFT/PTY button **S**, the stations are recalled in the order A1 to A8, B1 to B8, and so on, through E8.

4. RDS search (for FM only)

Use this function to automatically tune to stations offering Radio Data Service. This operation is also possible by pressing the TUNER button on the remote control unit once when the function is set to the TUNER mode.

Operation	Display
1. Press the RDS button R once.	RDS SEARCH
2. Press the PRESET UP or DOWN button P .	"RDS SEARCH" flashes on the display. (Preset memory channels A1 to E8 are being searched.) If no RDS station is found with the above operation, all the reception bands are searched. The station name is displayed after searching stops.
3. Press the PRESET UP or DOWN button again while the RDS mark is flashing.	RDS search starts again.

If no other RDS station is found when all the frequencies are searched, "NO RDS" is displayed.

5. PTY search (for FM only)

Use this function to find stations broadcasting a designated type of programme type (PTY). This operation is also possible by pressing the TUNER button on the remote control unit twice when the function is set to the TUNER mode. Next, press the PANEL button on the remote control unit, select the PTY, then press the PRESET UP or DOWN buttons to start the PTY search function in the specified direction.

Operation	Display
1. Press the RDS button twice.	PTY SEARCH
2. Press the SHIFT/PTY button.	Programme type or PTY (Designated programme type [Always do this to designate the programme type if "PTY" is displayed in step 1.]
3. Press the PRESET UP or DOWN button P .	"PTY SEARCH" flashes on the display. (Preset memory channels A1 to E8 are being searched.) If there is no station broadcasting the designated programme type with the above operation, all the reception bands are searched. The station name is displayed after searching stops.
4. Press the PRESET UP or DOWN button again while the PTY mark is flashing.	PTY search starts again.

If no other station broadcasting the designated programme type is found when all the frequencies are searched, "NO PROGRAMME" is displayed.

The programme types which can be displayed are listed on Page 13.

6. TP Search (for FM only)

This function is used to find stations scheduled to broadcast traffic programmes (TP stations). This operation is also possible by pressing the TUNER button on the remote control unit three times when the function is set to the TUNER mode.

Operation	Display
1. Press the RDS button R 3 times.	TP SEARCH
2. Press the PRESET UP or DOWN button P .	"TP SEARCH" flashes on the display. (Preset memory channels A1 to E8 are being searched.) If no TP station is found with the above operation, all the reception bands are searched. The station name is displayed after searching stops.
3. Press the PRESET UP or DOWN button again while the TP mark is flashing.	TP search starts again.

If no other TP station is found when all the frequencies are searched, "NO PROGRAMME" is displayed.

7. Writing station names

You can write in station names yourself. (Up to 8 characters)
(Refer to the table of characters on page 13.)

Operation	Display
1. Press the RDS button 4 times.	First character flashes.
2. Use the TUNING and DOWN buttons T to select the desired characters.	First letter flashes.
3. Use the SHIFT/PTY button S to move to the next place.	Specified place flashes.
4. After writing the entire station name, store it in the memory. (Refer to page 8.)	

RDS Emergency Alarm

"ALARM" will flash on the display when the unit receives the Emergency Programme Type Code (PTY31) from an RDS station. This feature may not operate properly if the signal from the RDS station is too weak or is subjected to interference. It is not possible to select the "ALARM" display from the PTY search mode.

8. Clearing station names

- Recall the station name you want to clear.
- Press the RDS button 4 times until the character at the first place flashes.
- Then press the SHIFT/PTY button for at least 2 seconds. The current station name will then be cleared.

Note: Station names must be stored in a preset memory to be retained. If the power is turned off, or if the band (AM/FM) is changed, the station name will be lost. Be sure to store the entered station name in a Preset Memory before changing the band or turning the power switch OFF.

The following programme types can be designated:

NEWS	NEWS	M.O.R MUSIC	M.O.R MUSIC
AFFAIRS	AFFAIRS	L-CLASSICS	LIGHT CLASSICS
INFORMATION	INFORMATION	S-CLASSICS	SERIOUS CLASSICS
SPORT	SPORT	OTHER MUSIC	OTHER MUSIC
EDUCATION	EDUCATION		
DRAMA	DRAMA		
CULTURE	CULTURE		
SCIENCE	SCIENCE		
VARIED	VARIED		
POP MUSIC	POP MUSIC		
ROCK MUSIC	ROCK MUSIC		

Table of characters

The characters are input in the order shown to the right. Use the TUNING buttons **T** to select the desired characters.

→ A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
→ 0 1 2 3 4 5 6 7 8 9 C \ / - & ' () * + , . / = SPACE

PLAYBACK USING THE REMOTE CONTROL

The accessory RC-174 remote control unit is used to control the RECEIVER from a distance.

(1) Inserting the dry cell batteries

- 1 Remove the rear cover on the remote control unit.




- 2 Insert two size "AA" (R6) dry cell batteries as shown in the diagram on the battery supply unit.



- 3 Replace the rear cover.



(2) Directions for use



Note on Operation

- Do not press the operating buttons on the receiver and the remote control unit at the same time. This will cause misoperation.
- Operation of the remote control unit will become less effective or erratic if the infrared remote control sensor on the receiver is exposed to strong light or if there are obstructions between the remote control unit and the sensor.
- In case you operate your VCR, TV or other components by remote control, do not operate buttons on two different remote control units at the same time. This will cause misoperation.

Notes on Use of the Batteries

- The remote control unit uses size "AA" (R6) dry cell batteries.
- The batteries will need to be replaced approximately once a year. This will depend upon how often the remote control is used.
- If, in less than a year from the time new batteries were inserted, the remote control fails to operate the receiver from a near-by position, it is time to replace the batteries.
- Insert the batteries properly, following the diagram on the remote control battery supply unit, and making sure to align the plus and minus sides of each battery.
- Batteries are prone to damage and leakage. Therefore:
 - Do not combine new batteries with used ones.
 - Do not combine different types of batteries.
 - Do not jumper the opposite poles of the batteries, expose them to heat or break them open, or put them into open fire.
- When the remote control is not to be used for a long period of time, remove the batteries from the unit.
- If the batteries have leaked, remove any battery fluid from the inside of the battery supply unit by wiping it out thoroughly, and insert new batteries.

Besides being able to operate the DRA-565RD/365RD receiver with this remote control unit, you can also operate a DENON cassette deck and CD player from this handy full-system remote control unit.

Remote Control Section

Full-system Remote Control Unit

The full-system remote control unit operates all major functions of the receiver such as function switching, volume control, and preset station selection. But that's not all! The same control pad can also control the major functions of a DENON CD player and cassette deck to create a remarkably ergonomic and versatile DENON system with all the quality sound reproduction that the devoted audiophile expects.

Remote Control Unit RC-174 supplied with DRA-565RD/365RD

DECK

▶ PLAY	PLAY button
◀ PLAY (REV)	PLAY (REV) button
■ STOP	STOP button
◀ REW	REWIND button
FF ▶▶	FF button
● REC	Refer to the operating instructions of your DENON tape deck.
⏸ PAUSE	PAUSE button
A/B W-DECK	A/B DECK SELECT button

PANEL button


The display switches between the frequency, manual characters, station name, programme type and time each time this button is pressed. Station names, programme types and the time are only displayed when receiving RDS stations.

The following may appear on the display for some stations, but this is not a malfunction: "NO PTY": This is an RDS broadcast, but the program type (PTY) is not being broadcast.

"NO PS": An RDS broadcast is being received, but the PS (Programme Service name or station name) is not being received due to weak signals, etc.

"NO TIME DATA": This is displayed when the station currently tuned in is not broadcasting time data, and may be displayed for one minute after the power is turned on even when the station currently tuned in is broadcasting time data.

(The PANEL button only operates when the function is set to the TUNER mode.)



- The RC-174 Remote Control Unit can control CD players and cassette decks made by DENON.
- Note that operation may not be possible for some models.
- Buttons are conveniently separated into groups, each group controlling one specific component. The groups are RECEIVER, CD and DECK.

For details on operating other components, refer to the instruction manuals for the CD player and/or cassette deck.

CAUTION:

- If the power is turned off with the remote control unit, the receiver is switched to the power stand-by state. If you are to be absent for a long period of time, be sure to turn the power off using the POWER switch on the receiver.
- A part of 1st digit of fluorescent display light while the receiver is in the power stand-by state.
- You may experience erratic operation of the remote control unit if it is operated in fluorescent light and direct sunlight, in particular if this light strikes the remote control sensor on the receiver. However, this is not a malfunction, and if this should happen, protect the sensor against such light.

TROUBLESHOOTING

1. Have all connections been made PROPERLY?
2. Have you followed all operational instructions correctly?
3. Check speaker and the turntable systems for proper operation.

When your unit does not seem to be operating correctly, first check the items in the following table. If the symptom does not correspond to any of the problems as shown below, turn off the power sources immediately and contact your DENON dealer.

Problem	Cause	Remedy
FM AND AM RECEPTION		
Radio program can not be received.	<ul style="list-style-type: none"> • Antenna connection is wrong. • A signal strength is weak. 	<ul style="list-style-type: none"> • Check the connection. • Check the antenna installation.
Noise is reproduced.	<ul style="list-style-type: none"> • A signal strength is weak. • Automobile ignition noise interferes with reception. • Other electrical equipment interferes with reception. 	<ul style="list-style-type: none"> • Install an outdoor antenna. • Keep the antenna away from the street. • Keep the equipment away from this set, or turn off the power of the other equipment.
The preset frequencies are erased.	<ul style="list-style-type: none"> • The memory back-up term (about 1 month) passed. 	<ul style="list-style-type: none"> • Preset again.
In automatic tuning, the frequency doesn't stop at the radio station.	<ul style="list-style-type: none"> • A signal strength is weak. 	<ul style="list-style-type: none"> • Use manual tuning.
In automatic tuning, it stops at the one step lower or higher frequency than the radio station.	<ul style="list-style-type: none"> • Noise or strong signal strength is received. 	<ul style="list-style-type: none"> • Use manual tuning for optimum reception.
PLAYBACK OF THE AUDIO EQUIPMENTS		
No sound is produced with power on.	<ul style="list-style-type: none"> • Input and speaker cords connection are wrong. • Speaker switch is off. • The INPUT SELECTOR buttons are in wrong position. • The protective circuit is operating. • The fuse has blown out. 	<ul style="list-style-type: none"> • Check the connection. • Turn on speaker switch. • Check these position. • Turn the power off once, check the connections to the speakers, then turn the power on again. • Ask your dealer, or the nearest DENON representative.
Audible hum when playing records.	<ul style="list-style-type: none"> • The input and grounding cords connection of the turntable are wrong. • The cords connection of the cartridge are wrong. • The interference from the nearby TV or radio transmission antenna. 	<ul style="list-style-type: none"> • Check the connection. • Check the connection. • Ask your dealer, or the nearest DENON representative.
Howling is produced when the volume control is turned up too high while playing records.	<ul style="list-style-type: none"> • The vibrations and sounds transmit from the speakers to the turntable. 	<ul style="list-style-type: none"> • Insulate the vibrations, or keep the speakers away from the turntable.
Cracking noise is produced when playing records.	<ul style="list-style-type: none"> • The record is stained with the dust. • The stylus tip of the cartridge is stained with the dust. • The cartridge is defective. 	<ul style="list-style-type: none"> • Clean the record. • Clean the stylus tip. • Try the other cartridge.

SPECIFICATIONS

AMPLIFIER SECTION

Continuous Power Output: **DRA-565RD: 80 W + 80 W (4 ohms, 1 kHz)**
DRA-365RD: 82 W + 82 W (4 ohms, 1 kHz)
Power Bandwidth (BW): 10 Hz ~ 40 kHz (T.H.D. 0.1% both channels driven into 8 ohms)

Total Harmonic Distortion: 0.03% (-3 dB at rated output, 8 ohms)
Frequency Response: PHONO RIAA Standard Curve (Recording Output)

MM 20 Hz ~ 20 kHz ± 0.5 dB
CD, VIDEO, 20 Hz ~ 60 kHz ± 1.5 dB (at 1W)
TAPE-1, TAPE-2 (DRA-565RD)
TAPE (DRA-365RD)

Input Sensitivity and Impedance: PHONO MM 2.5 mV 47 k ohms
CD, VIDEO, 150 mV 25 k ohms
TAPE-1, TAPE-2 (DRA-565RD)
TAPE (DRA-365RD)

Maximum Input Level (at 1 kHz): PHONO MM 120 mV
Signal to Noise Ratio (BW-A): PHONO MM 78 dB (at 5.0 mV input)
CD, VIDEO, 95 dB
TAPE-1, TAPE-2 (DRA-565RD)
TAPE (DRA-365RD)

Tone Controls: BASS ± 10 dB at 100 Hz
TREBLE ± 10 dB at 10 kHz
Loudness Control Effect: VARIABLE LOUDNESS at maximum position
50 Hz/10 kHz, ± 10 dB ± 8 dB

PRE-OUT (terminals): Rated output: 2 V (at 100 kohm load)
(DRA-565RD only)

TUNER SECTION

(FM) (note: μ V at 75 ohms, 0 dB/ -1×10^{-15} W)
Receiving Range: 87.5 ~ 108 MHz
Usable Sensitivity: 0.5 μ V (10.3 dB)

Signal to Noise Ratio (BW-A): MONO 82 dB
STEREO 78 dB

Image Rejection: 85 dB
Selectivity (± 300 kHz): 55 dB

Frequency Response: 30 Hz ~ 15 kHz ± 0.2 dB

Stereo Separation (at 1 kHz): 40 dB

(AM) Receiving Range: 522 ~ 1611 kHz

Usable Sensitivity: 18 μ V
Signal to Noise Ratio: 55 dB

General Power Supply: AC 230V 50 Hz

Power Consumption: 145 W (DRA-565RD)
120 W (DRA-365RD)

Power Outputs: SWITCHED 100 W

Dimensions: 434 mm (W) \times 130 mm (H)
 \times 312 mm (D) (DRA-565RD)

434 mm (W) \times 120 mm (H)
 \times 312 mm (D) (DRA-365RD)

Weight: 7.2 kg (DRA-565RD)
6.9 kg (DRA-365RD)

REMOTE CONTROL UNIT RC-174

Remote control system: Infrared pulse system
Power supply: 3V DC Two size "AA" (R6)
dry cell batteries

External dimensions: 80 mm W \times 175 mm H
 \times 18 mm D

Weight: 120 g (includes batteries)


Design and specifications are subject to change without prior notice.

DISASSEMBLY

(To reassemble reverse disassembly)


● Top Cover

Remove 4 screws ① and 2 screws ②.




● Front Mold Panel

- (1) Pull out Volume knob ④ and 4 round knobs ⑤.
- (2) Remove 5 nuts ⑥ and Speed Nut ⑦.
- (3) Remove 2 screws ⑧.



● Front Aluminium Panel


Remove 4 screws (365RD) 5 screws (565RD) ③ and undo hooks at 4 places.




● Rear Panel

- (1) Disconnect cord bush ⑨.
- (2) Remove 7 screws ⑩, and 8 screws (365RD) 9 screws (565RD) ⑪.

*Screws 11 is tighten.




- Despite the transformer and PWB are connected with the wire, an arrangement clumper is relatively easy to remove at a time of service.




- (1) Disassemble Front Aluminium Panel (refer to previous item 2).
- (2) Remove 4 screws (D) securing the Radiator to the Bottom Cover.
- (3) Unfasten 2 screws on the surface and 5 screws on the bottom of Rear Panel (refer to previous item 4).
- (4) Remove 2 screws (A) securing the Inner Panel.
- (5) Untighten a screw (C) and detach Main PWB, remove a screw (B) and detach Power Supply PWB.
- (6) Remove arrangement clumper for the wire of Transformer.
- (7) Hold and lift the Back Panel and Inner Panel.

Checking is feasible by positioning the PWB upright.



METHOD OF ADJUSTMENTS



IDLING CURRENT

(1) Set controls as follows.

- POWER Switch → off ()
 VOLUME Control → 0 (min.)
 SPEAKERS → off ()
 Temperature → 15°C ~ 30°C (59°F ~ 86°F)
 VR305 and VR306 of the 1U-2718-1 (Main Unit) → MIN. ()

(2) Connect DC Voltmeter to the T.P. Lch and T.P. Rich of the 1U-2718.


(3) Turn the Power Switch on and rotate VR305 clockwise so that the DC Voltmeter reads 2.5 mV \pm 0.2 mV DC at the T.P. Lch. Follow the same procedure to VR306 for T.P. Rich.

(4) Warm up for three minutes, then readjust VR305 and VR306 so that the DC Voltmeter reads 2.5 mV \pm 0.5 mV DC.


(5) Warm up for 10 minutes, then readjust VR305 and VR306 so that the DC Voltmeter reads 2.5 mV \pm 0.5 mV DC.

CONNECTINON DIAGRAM OF MEASURING INSTRUMENTS

● FM SECTION



● AM SECTION





Adjust T503 for maximum height and best symmetry curve.

SEMICONDUCTORS

● IC's

TMP87CM71F (IC601)





TMP87CM71F Port Allocation Table

Pin No.	Symbol	I/O	Logic	Initial Setting	Function
1	STOP	I	L	—	Power down detection ("L" = at power down).
2	MUTE (A)	I	—	—	MUTE (A) output ("H" = MUTE).
3	RDS	I	Serial	—	RDS data (start) input.
4	RES	O	L	H	LC7074 reset output.
5	GND	I	Serial	—	Not used.
6	FCK	O	Serial	L	Function control output (LC7821) for F-CK.
7	FDA	O	Serial	L	Function control output (LC7821) for F-DATA.
8	FSTB	O	H	L	Function control output (LC7821) for F-STB.
9	GND	I	—	—	Connect to GND.
10	SD	I	L	—	Tuned signal input ("L" = at tuned in).
11	GND	I	—	—	Not used.
12	RESET	I	L	—	Reset input.
13	XIN	I	—	—	Oscillation circuit (4MHz).
14	XOUT	I	—	—	Oscillation circuit (4MHz).
15	Vss	PW	—	—	GND.
16	GND	I	—	—	GND.
17	REM	I	L	—	Remote control signal input.
18	ST	I	L	—	Stereo signal input ("L" = at stereo).
19	RCK	I	Serial	—	RDS data (clock) input.
20	RDA	I	Serial	—	RDS data (data) input.
21	GND	I	—	—	Not used.
22	PCK	O	Serial	L	LM7001 control output for PLL-CK (CL).
23	PDA	O	Serial	L	LM7001 control output for PLL-DATA (DATA).
24	PSTB	O	H	L	LM7001 control output for PLL-STB (CE).
25	GND	O	—	L	GND.
26	GND	O	—	L	GND.
27	A/M	O	L	L	AUTOMANUAL control.
28	GND	I	—	—	Not used.
29	P.OF	O	H	L	Power control output ("H" = ON).
30	VR-UP	O	H	L	Power volume control output (LB1639 ON = at "H").
31	VR-D	O	H	L	Power volume control output (LB1639 ON = at "H").
32	SP-R	O	H	L	Speaker relay control output (ON = at "H").
33	Vcc	PW	—	—	+5V.
34	GND	I	—	—	GND.
35	GND	I	—	—	GND.
36	1G	O	—	—	FL tube control output for 1G.
37	2G	O	—	—	FL tube control output for 2G.
38	3G	O	—	—	FL tube control output for 3G.
39	4G	O	—	—	FL tube control output for 4G.

Pin No.	Symbol	I/O	Logic	Initial Setting	Function
40	5G	O	—	—	FL tube control output for 5G.
41	6G	O	—	—	FL Tube control output for 6G.
42	7G	O	—	—	FL Tube control output for 7G.
43	8G	O	—	—	FL Tube control output for 8G.
44	9G	O	—	—	FL Tube control output for 9G.
45	10G	O	—	—	FL Tube control output for 10G.
46	11G	O	—	—	FL Tube control output for 11G.
47	12G	O	—	—	FL Tube control output for 12G.
48	13G	O	—	—	FL Tube control output for 13G.
49	14G	O	—	—	FL Tube control output for 14G.
50	S0 (a)	O	—	—	FL Tube control output for P(a).
51	S1 (b)	O	—	—	FL Tube control output for P(b).
52	S2 (c)	O	—	—	FL Tube control output for P(c).
53	S3 (d)	O	—	—	FL Tube control output for P(d).
54	S4 (e)	O	—	—	FL Tube control output for P(e).
55	S5 (f)	O	—	—	FL Tube control output for P(f).
56	S6 (g)	O	—	—	FL Tube control output for P(g).
57	S7 (h)	O	—	—	FL Tube control output for P(h).
58	S8 (i)	O	—	—	FL Tube control output for P(i).
59	S9 (k)	O	—	—	FL Tube control output for P(k).
60	S10 (m)	O	—	—	FL Tube control output for P(m).
61	S11 (n)	O	—	—	FL Tube control output for P(n).
62	S12 (p)	O	—	—	FL Tube control output for P(p).
63	S13 (q)	O	—	—	FL Tube control output for P(q).
64	S14 (r)	O	—	—	FL Tube control output for P(r).
65	S15 (s)	O	—	—	FL Tube control output for P(s).
66	Vkk	PW	—	—	-15V.
67					
68					
69					
70	GND	I	—	—	GND.
71	VA	O	L	H	Video In/Out control ("L" = at selection) BV4066.
72	VB	O	L	H	Video In/Out control ("L" = at selection) BV4066.
73	K1	I	—	—	Key input (A/D conversion input).
74	K2	I	—	—	Key input (A/D conversion input).
75	K3	I	—	—	Key input (A/D conversion input).
76	K4	I	—	—	Key input (A/D conversion input).
77	VER	I	—	—	Forwarding country setting.
78	VER	I	—	—	Specification setting.
79	MUTE (T)	O	H	H	MUTE output ("H" = MUTE).
80	GND	I	—	—	GND.


NJM78M12FA
(IC504)
NJM7806FA
(IC401)

SBX1610-52 (REMOTE SENSOR)



1. Vcc
2. Output
3. GND
4. Case Fin
5. Case Fin

STANDARD
TRANSMITTER



IC1 : CX20106A Chip
D1 : PIN Photo Diode Chip
C1, C2, C4 : Aluminum Electrolytic Capacitor
C3 : SL Characteristic ±5%
R1 : Gain Adjuster
R2 : to Adjust ±1% USE
R3, R4 : ±5%

TRANSISTORS






2SA988(E/F)
2SA1515(R)
2SC1815(Y)
2SC1841(E/F)

2SB647A(C)
2SB1041(R)
2SD667A(C)

2SA933S(S)
2SA1038S(S/E)
2SC1740S(E)
2SC1740SLN(E)
2SC2058(Q)
2SC2389S(S/E)

2SB1328(P)
2SD2004(P)

2SK161(GR)








2SA1489(O/P/Y)(Z)
2SA1491(O/P/Y)(Z)
2SC3853(O/P/Y)(Z)
2SC3855(O/P/Y)(Z)

DTA143ES(4.7K-4.7K)
DTA114ES(10K-10K)
DTB123ES
DTC143ES(4.7K-4.7K)
RN-1241(A/B)
DTC144ES(47K-47K)

2SK365 (BL/GR)
DTC143ES
DTA143ES
DTB123ES



DTC143ES

RN1241



DTA143ES

DTB123ES






DIODES & LED

1SS252

1S2471




MTZJ3.3A MTZJ7.5C
MTZJ6.2A MTZJ8.2B
MTZJ6.8C MTZJ27D






1SR35-200A

S4VB20

SFOR1A42



FLD (FIP14AM7R)



TERMINAL CONNECTION
(UPPER)



TERMINAL NO.	68	67	66	65	64	63	62	61	60	59	58	57	56	55	54	53	52
ELECTRODE	F1	F1	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP
TERMINAL NO.				51	50	49	48	47	46	45	44	43	42	41	40	39	38
ELECTRODE				NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP	NP

(LOWER)



TERMINAL NO.				18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34
ELECTRODE				P	14G	13G	12G	11G	10G	9G	8G	7G	6G	5G	4G	3G	2G	1G	F2	F2
TERMINAL NO.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17			
ELECTRODE	F1	F1	P	P	P	P	P	P	P	P	P	P	P	P	P	P	P			

Notes : F : Filament
G : Grid
P : Anode

BLOCK/LEVEL DIAGRAM (DRA-565RD)



BLOCK/LEVEL DIAGRAM (DRA-365RD)



NOTE FOR PARTS LIST

- Part indicated with the mark "●" are not always in stock and possibly to take a long period of time for supplying, or in some case supplying of part may be refused.
- When ordering of part, clearly indicate "I" and "I" (i) to avoid mis-supplying.
- Ordering part without stating its part number can not be supplied.
- Part indicated with the mark "*" is not illustrated in the exploded view.
- Not including Carbon Film $\pm 5\%$, 1/4W Type in the P.W.Board parts list. (Refer to the Schematic Diagram for those parts.)

WARNING:

Parts marked with this symbol Δ have critical characteristics.
Use ONLY replacement parts recommended by the manufacturer.

● Resistors

Ex.: RN 14K 2E 182 G FR Others
Type Shape and performance Power Resistance Allowable error Others

RC : Carbon	2B : 1/8W	F : $\pm 1\%$	P : Pulse-resistant type
RC : Composition	2E : 1/4W	G : $\pm 2\%$	RL : Low noise type
RS : Metal oxide film	2H : 1/2W	J : $\pm 5\%$	NB : Non-burning type
RW : Winding	3A : 1W	K : $\pm 10\%$	PR : Fuse-resistor
RH : Metal film	3D : 2W	M : $\pm 20\%$	F : Lead wire forming
RE : Metal mixture	3F : 3W		
	3H : 5W		

● Resistance

1 8 2 = 1800 ohm = 1.8 kohm
Indicates number of zeros after effective number.
2-digit effective number.

Units: ohm

1 R 2 = 1.2 ohm

1-digit effective number.
2-digit effective number, decimal point indicated by R.

Units: ohm

● Capacitors

Ex.: CE 04W 1H 2R2 M BP Others
Type Shape and performance Dielectric strength Capacity Allowable error Others

CE : Aluminum foil electrolytic	0J : 6.3V	F : $\pm 1\%$	HS : High stability type
CA : Aluminum solid electrolytic	1A : 10V	G : $\pm 2\%$	BP : Non-polar type
CS : Tantalum electrolytic	1C : 18V	J : $\pm 5\%$	HR : Ripple-resistant type
CO : Film	1E : 30V	K : $\pm 10\%$	OL : For charge and discharge
CK : Ceramic	1V : 35V	M : $\pm 20\%$	NF : For assuring high frequency
CC : Ceramic	1H : 50V	Z : $\pm 80\%$	U : UL part
CP : Oil	2A : 100V	P : $\pm 100\%$	C : CSA part
CM : Mica	2B : 125V	D : $\pm 0.5\mu\text{F}$	W : UL-CSA type
CF : Metallized	2C : 160V	C : $\pm 0.5\mu\text{F}$	F : Lead wire forming
CH : Metallized	2D : 200V	= : Others	
	2E : 250V		
	2H : 500V		
	2J : 630V		

● Capacity (electrolyte only)

2 2 2 = 2200 μF
Indicates number of zeros after effective number.
2-digit effective number.

Units: μF

2 R 2 = 2.2 μF

1-digit effective number.
2-digit effective number, decimal point indicated by R.

Units: μF

● Capacity (except electrolyte)

2 2 2 = 2200pF = 0.0022 μF
(More than 2) — Indicates number of zeros after effective number.
2-digit effective number.

Units: pF

2 2 1 = 220pF

(0 or 1) — Indicates number of zeros after effective number.
2-digit effective number.

Units: pF

● When the dielectric strength is indicated in AC, "AC" is included after the dielectric strength value.

PRINTED WIRING BOARD PARTS LIST
1U-2731B MAIN UNIT (DRA-565RD)

Ref. No.	Part No.	Part Name	Remarks	Ref. No.	Part No.	Part Name	Remarks
SEMICONDUCTORS GROUP				CAPACITORS GROUP			
IC101	263 0609 002	IC NJM2068DDC		△ R387-390	241 2377 989	Carbon 150ohm 1/4W	RD1482E151JNBS
IC102	262 1227 006	IC LC7821		△ R391-394	244 2051 967	Metallic 4.7ohm 1W	RS1483A47JNBS(S)
IC201	263 0476 002	IC LB1639		△ R401	244 2051 987	Metallic 4.7ohm 1W	RS1483A47JNBS(S)
IC301	263 0565 007	IC BA15218		△ R403	244 2055 954	Metallic 150ohm 1W	RS1483A151JNBS(S)
IC401	263 0793 002	IC NJM7806FA(S)		△ R408	241 2387 908	Carbon 1ohm 1/4W	RD1482E01JNBS
IC601	262 1701 906	IC SA46579T		△ R411	241 2377 947	Carbon 100ohm 1/4W	RD1482E01JNBS
IC602	262 1929 908	IC LC704NM-TE-R		△ R471	244 2055 996	Metallic 12ohm 1W	RS1483A122JNBS(S)
				△ R474	244 2051 990	Metallic 4.7ohm 1W	RS1483A47J2JNBS(S)
TR201	269 0022 904	Transistor DTA143ES(4.7K-4.7K)		VR102	211 0831 002	Variable 100kohm	V1620V25F-104R(MG)
TR251	274 0151 903	Transistor 2SD2004(P)		VR201	211 0830 003	Variable 100kohm	V14V20FB104K
TR252	272 0107 906	Transistor 2SB1328(P)		VR251	211 0827 003	Variable 250kohm	V11V20FW254K
TR253	273 0388 906	Transistor 2SC1740S(E)		VR301	211 0828 002	Variable 250kohm	V14V20FC254K
TR254	271 0192 905	Transistor 2SA933S(S)		VR303	211 0829 001	Variable 50kohm	V14V20FC503K
TR255	273 0432 904	Transistor 2SC2389S(S/E)		VR305,306	211 6093 912	Semr Fixed Resistor 4.7kohm	V06P9472
TR256	271 0280 901	Transistor 2SA1038S(S/E)					
TR257	273 0388 906	Transistor 2SC1740S(E)					
TR301,302	269 0107 900	Transistor RH1241(A/B)					
TR303,304	273 0235 923	Transistor 2SC1841(E/F)					
TR305-308	271 0131 924	Transistor 2SA988(E/F)					
TR309,310	273 0235 923	Transistor 2SC1841(E/F)					
TR315,316	273 0198 002	Transistor 2SC1815(Y)					
TR317,318	274 0151 903	Transistor 2SD2004(P)					
TR319,320	272 0107 906	Transistor 2SB1328(P)					
TR325,326	273 0235 923	Transistor 2SC1841(E/F)					
TR327	271 0131 924	Transistor 2SA988(E/F)					
TR401	272 0131 901	Transistor 2SB1041(R)					
TR402,403	273 0388 906	Transistor 2SC1740S(E)					
TR451	273 0388 906	Transistor 2SC1740S(E)					
TR452	269 0018 905	Transistor DTC143ES(4.7K-4.7K)					
TR453	273 0388 906	Transistor 2SC1740S(E)					
TR472,473	273 0388 906	Transistor 2SC1740S(E)					
TR474	271 0192 905	Transistor 2SA933S(S)					
TR475	273 0388 906	Transistor 2SC1740S(E)					
TR476,479	269 0040 902	Transistor DTC144ES(4.7K-4.7K)					
D202-204	276 0616 907	Diode 1SS252					
D303-306	276 0619 904	Diode 1S2471					
D307-312	276 0616 907	Diode 1SS252					
D401	276 0616 907	Diode 1SS252					
D402-404	276 0553 905	Diode 1SR35-200A					
D405	276 0338 007	Diode S4VR20F					
D406	276 0616 907	Diode 1SS252					
D407-410	276 0553 905	Diode 1SR35-200A					
D451	276 0616 907	Diode 1SS252					
D452	276 0616 907	Diode 1SS252					
D471	276 0616 907	Diode 1SS252					
ZD251,252	276 0637 902	Zener Diode MTZJ6.2A					
ZD401	276 0632 907	Zener Diode MTZJ27D					
ZD451	276 0634 905	Zener Diode MTZJ3.3A					
ZD452	276 0633 906	Zener Diode MTZJ6.8C					
ZD471	276 0635 904	Zener Diode MTZJ7.5C					
SC471	279 0016 904	Thyristor SF0R1A42					
RESISTORS GROUP							
△ R205-208	244 2050 933	Metallic 180ohm 1W	RS1483A181JNBS(S)				
△ R209,266	241 2387 940	Carbon 4.7ohm 1/4W	RD1482E4R7JNBS				
△ R311,312	241 2378 932	Carbon 20ohm 1/4W	RD1482E62JNBS				
△ R329,330	241 2375 920	Carbon 220ohm 1/4W	RD1482E22JNBS				
△ R331-338	244 2043 982	Metallic 0.22ohm 1W	RS1483A022JNBS(S)				
△ R343-346	241 2378 987	Carbon 11ohm 1/4W	RD1482E10JNBS				
△ R385,386	241 2378 932	Carbon 62ohm 1/4W	RD1482E62JNBS				

1U-2732B TUNER UNIT (DRA-565RD)

Ref. No.	Part No.	Part Name	Remarks
C353,354	256 1034 979	Film 0.01µF50V	CF93A1H104J
C371-374	256 1034 979	Film 0.01µF50V	CF93A1H104J
C377,378	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C401	259 0007 702	For Back up 8200µF	S8 CAP=822-C
C402	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C403	254 4257 702	Electrolytic 3000µF25V	CE04W1E32M
C404	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C405	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C406,407	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C408,409	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C415,416	254 4374 708	Electrolytic 8200µF50V	CE04W1E32M(DL)
C418	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C419	256 1042 903	Film 0.01µF25V	CF93A2E104K
C451	254 4258 905	Electrolytic 4.7µF35V	CE04W1V4R7M
C452	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C458	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C471	254 4260 980	Electrolytic 10µF50V	CE04W1H100M
C472	254 4260 993	Electrolytic 22µF50V	CE04W1H22M
C473	254 4250 945	Electrolytic 330µF6.3V	CE04W0J331M
C480	253 1146 907	Ceramic 0.01µF50V	CK45F1H103Z
C501,502	253 1311 907	Ceramic 27pF50V	CC45C1H1270J
C503-505	254 4250 918	Electrolytic 47µF6.3V	CE04W0J470M
C507,508	253 4537 911	Ceramic 30pF50V	CC45SL1H300J
C508	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C510	254 4250 918	Electrolytic 47µF6.3V	CE04W0J470M
C511	253 1178 990	Ceramic 560pF50V	CK45B1H561K
OTHERS PARTS GROUP			
L101,102	235 9003 002	FTZ Choke Coil	1µH
L391,392	235 0068 004	Inductor	
RL471	214 9003 005	Relay	TEST POINT
TP301,302	205 0190 036	3P NH Connector Base	
XL501	399 0178 007	Crystal	4.332MHz
XL502	399 0041 901	Ceramic Filter	CSA 4.00MHz
CH2A-2A	205 0185 025	2P Wire Holder	CR3F Europe Model Only (Except for U.K.)
CH3B,3F	205 0343 032	3P Connector Base (KR-PH)	
CNSA-5A	205 0185 054	5P Wire Holder	Europe Model U.K. Model
CN7A	205 0696 077	J.L. Connector(BT-E)	
CN8A	205 0535 002	8P Connector Base	Europe Model U.K. Model
CN9B	205 0696 093	J.L. Connector(BT-E)	
CN9B	205 0746 093	9P J.L. Connector(R)	Europe Model U.K. Model
CN27A	205 0680 016	27P PFC Connector Base	
	203 0539 060	1P SIN Cord Assy	Europe Model U.K. Model
	203 0539 073	1P SIN Cord Assy	
	203 0539 086	1P SIN Cord Assy	Europe Model U.K. Model
	203 0539 099	1P SIN Cord Assy	
	203 0475 043	1P Contact Assy	Europe Model U.K. Model
	002 0012 081	2C Ribbon Cable	
	002 0041 010	5C Ribbon Cable	Europe Model U.K. Model
	415 0309 013	P.V.C. Tube(φ=10)	

Ref. No.	Part No.	Part Name	Remarks
SEMICONDUCTORS GROUP			
IC501	263 0891 001	IC LA1265(S)	
IC502	263 0439 007	IC LA3401	
IC503	262 0719 009	IC LM7001	
IC504	263 0801 004	IC NJM7812FA(S)	
IC601	263 2039 017	IC TMP87CM71F-6192	
TR501	275 0051 909	Transistor 2SK161(GR)	
TR502	273 0434 902	Transistor 2SC2058(SQ)	
TR503	269 0150 902	Transistor DTB123ES	
TR504	273 0435 901	Transistor 2SC1740SLN(E)	
TR505	275 0053 907	Transistor 2SK365(BUGR)	
TR506	269 0046 906	Transistor DTA114ES(10K-10K)	
TR507,508	269 0040 902	Transistor DTC144ES(47K-47K)	
TR509	271 0279 909	Transistor 2SA1515(R)	
D411	276 0616 907	Diode 1SS252	
ZD501	276 0636 903	Zener Diode MTZJ.8.2B	
ZD651	276 0636 903	Zener Diode MTZJ.8.2B	
RESISTORS GROUP (Not included Carbon Film ±5% 1/4W)			
CAPACITORS GROUP			
Δ C410	253 1014 702	Ceramic 0.01µF500V VAC	CK45F2GAC103MC
Δ C413	253 1014 702	Ceramic 0.01µF500V VAC	CK45F2GAC103MC
C501-505	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C506	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C507	253 4536 954	Ceramic 16pF50V	CC45SL1H160J
C508	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C509	253 1179 903	Ceramic 100pF50V	CC45B1H101K
C510-513	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C514	254 4256 936	Electrolytic 47µF25V	CE04W1E470M
C515	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C516	254 4260 964	Electrolytic 3.3µF50V	CE04W1H3R3M
C517	253 1181 917	Ceramic 0.022µF50V	CK45F1H222Z
C518	254 4260 922	Electrolytic 0.33µF50V	CE04W1HR33M
C519	253 1179 903	Ceramic 100pF50V	CC45B1H101K
C520	256 1034 937	Film 0.047µF50V	CF93A1H473J(B)
C521	253 9031 904	Ceramic 0.047µF25V	CK45=1E473K
C522,523	254 4254 912	Electrolytic 22µF16V	CE04W1C220M
C525	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C526,527	253 4446 903	Ceramic 330pF50V	CC45SL1H331J
C529	254 4254 908	Electrolytic 47µF16V	CE04W1H0R1M
C530	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C531	254 4260 919	Electrolytic 0.22µF50V	CE04W1HR22M
C532	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C533	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C534,535	254 4260 951	Electrolytic 2.2µF50V	CE04W1HR22M
C536	253 1146 907	Ceramic 0.01µF50V	CK45F1H103Z
C537	254 4260 906	Electrolytic 0.01µF50V	CE04W1H0R1M
C538	254 4254 938	Electrolytic 47µF16V	CE04W1C470M
C539	254 3056 917	Electrolytic 1µF50V	CE04D1H101MBP
C540	253 1181 917	Ceramic 0.022µF50V	CK45F1H222Z
C542,543	253 4536 954	Ceramic 16pF50V	CC45SL1H160J
C544	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C545	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C546	254 4254 938	Electrolytic 47µF16V	CE04W1C470M
C547	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C548	254 4260 980	Electrolytic 10µF50V	CE04W1H100M
C551-554	253 1146 907	Ceramic 0.01µF50V	CK45F1H103Z

1U-2731 MAIN UNIT (DRA-365RD)

Ref. No.	Part No.	Part Name	Remarks
C651	255 1265 949	Film 0.012µF50V	CO93M1H123J(B)
C652	254 4300 963	Electrolytic 100µF6.3V	CE04W0J101M
C653	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
OTHERS PARTS GROUP			
CF501,502	261 0064 007	Ceramic Filter	SFT10.7M32
CF503	261 0116 007	Ceramic Filter	SFL450B3
CF504	261 0101 009	Ceramic Filter	BFL450C4N
△ F401	206 1015 061	Fuse 2A	Europe Model Only (Except for U.K.)
△ F402	206 1015 029	Fuse 1A	
RL401	214 0176 009	Relay (G5P-1)	Europe Model Only (Except for U.K.)
RM601	499 0150 008	Remote Sensor	SBX1610-52
SW601-615	212 5604 910	Tact Switch	TV-5
△ SW401	212 1030 009	Power Switch	
TS01	231 1913 004	1MW Antenna Oscillator Coil	CSB456F11
TS02	231 2098 009	FM IF DET Trans	
TS03	231 1144 006	AM IFT	CST4.00MGW-TF01
TS04	232 9010 009	Antibiotic Filter	
TS05,506	232 0085 004	LPF	FIP14AM7R
XL502	261 0103 007	Ceramic Oscillator	
XL503	399 0075 003	Crystal	7.2Mhz
XL601	399 0191 903	Ceramic Oscillator	
	393 4155 002	FLD	Europe Model Only (Except for U.K.)
	205 0847 004	3P Antenna Terminal (PAL/F)	
	216 0065 006	Front End	Europe Model Only (Except for U.K.)
	205 0624 007	2P AC Connector Base	
CH30	205 0581 001	2P VH Connector Base	Europe Model Only (Except for U.K.)
CH3E	205 0581 056	2P VH Connector Base	
CH7A	205 0748 077	J.L. Connector(R)	Europe Model Only (Except for U.K.)
CH8A	205 0536 001	8P Connector Socket	
CH27A	205 0890 016	27P PFC Connector Base	Europe Model Only (Except for U.K.)
CH3B	203 2361 003	2P SAN-3P PH Connector Cord	
△	203 0543 051	1P Contact Assy	Europe Model Only (Except for U.K.)
△	203 0543 054	1P Contact Assy	
△	203 0543 057	1P PHSAN Connector Cord	Europe Model Only (Except for U.K.)
△	203 0543 058	1P PHSAN Connector Cord	
△	203 0543 059	2P VH Connector Cord	Europe Model Only (Except for U.K.)
△	202 0040 809	Fuse Clip	
RESISTORS GROUP			
△ R207,208	244 2052 931	Metallic 350ohm 1W	RD1483A391NBS(S)
△ R255,256	241 2387 940	Carbon 4.7ohm 1/4W	RD1483E470NBS
△ R311,312	241 2379 932	Carbon 620ohm 1/4W	RD1482E621NBS
△ R329,330	241 2378 820	Carbon 220ohm 1/4W	RD1482E221NBS
△ R331-334	244 2043 982	Metallic 0.22ohm 1W	RD1483AP221NBS(S)
△ R343,344	241 2379 987	Carbon 11ohm 1/4W	RD1482E102NBS
△ R345,346	241 2378 962	Carbon 330ohm 1/4W	RD1482E331NBS

Ref. No.	Part No.	Part Name	Remarks
SEMICONDUCTORS GROUP			
IC101	263 0609 002	IC NJM2068DOC	Europe Model Only (Except for U.K.)
IC102	262 1227 008	IC LC7821	
IC201	263 0476 002	IC LB1633	Europe Model Only (Except for U.K.)
IC301	263 0565 007	IC BA15218	
IC401	263 0793 002	IC NJM7806FA(S)	Europe Model Only (Except for U.K.)
IC601	262 1701 906	IC SAA579T	
IC602	262 1929 908	IC LC7074M-TE-R	Europe Model Only (Except for U.K.)
TR201	269 0022 904	Transistor DTA143ES(4.7K-4.7K)	
TR251	274 0151 903	Transistor 2SD2004(P)	Europe Model Only (Except for U.K.)
TR252	272 0017 906	Transistor 2SB1328(P)	
TR253	273 0388 906	Transistor 2SC1740S(E)	Europe Model Only (Except for U.K.)
TR254	271 0192 905	Transistor 2SA933S(S)	
TR255	273 0432 904	Transistor 2SC2385S(S/E)	Europe Model Only (Except for U.K.)
TR256	271 0280 901	Transistor 2SA1038S(S/E)	
TR257	273 0388 906	Transistor 2SC1740S(E)	Europe Model Only (Except for U.K.)
TR301,302	269 0107 900	Transistor RN1241 (A/B)	
TR303,304	273 0235 923	Transistor 2SC1841(E/F)	Europe Model Only (Except for U.K.)
TR305-308	271 0131 924	Transistor 2SA988(E/F)	
TR309,310	273 0235 923	Transistor 2SC1841(E/F)	Europe Model Only (Except for U.K.)
TR315,316	273 0198 002	Transistor 2SD1815(T)	
TR317,318	274 0060 900	Transistor 2SD667A(C)TZ	Europe Model Only (Except for U.K.)
TR319,320	272 0053 908	Transistor 2SB647A(C)	
TR325,326	273 0235 923	Transistor 2SC1841(E/F)	Europe Model Only (Except for U.K.)
TR327	271 0131 924	Transistor 2SA988(E/F)	
TR401	272 0131 901	Transistor 2SB1041(R)	Europe Model Only (Except for U.K.)
TR451	273 0388 906	Transistor 2SC1740S(E)	
TR452	269 0018 905	Transistor DTC143ES(4.7K-4.7K)	Europe Model Only (Except for U.K.)
TR453	273 0388 906	Transistor 2SC1740S(E)	
TR472,473	273 0388 906	Transistor 2SC1740S(E)	Europe Model Only (Except for U.K.)
TR474	271 0192 905	Transistor 2SA933S(S)	
TR475	273 0388 906	Transistor 2SC1740S(E)	Europe Model Only (Except for U.K.)
TR478,479	269 0040 902	Transistor DTC144ES(4.7K-4.7K)	
D202-204	276 0616 907	Diode 1SS252	Europe Model Only (Except for U.K.)
D303-306	276 0619 904	Diode 1SS2471	
D307-310	276 0616 907	Diode 1SS252	Europe Model Only (Except for U.K.)
D311,312	276 0616 907	Diode 1SS252	
D401	276 0616 907	Diode 1SS252	Europe Model Only (Except for U.K.)
D402-404	276 0553 905	Diode 1SR35-200A	
D405	276 0339 007	Diode 54VB20F	Europe Model Only (Except for U.K.)
D406	276 0616 907	Diode 1SS252	
D407-410	276 0553 905	Diode 1SR35-200A	Europe Model Only (Except for U.K.)
D451	276 0616 907	Diode 1SS252	
D452	276 0616 907	Diode 1SS252	Europe Model Only (Except for U.K.)
D471	276 0616 907	Diode 1SS252	
ZD251,252	276 0637 902	Zener Diode MTZ.6.2A	Europe Model Only (Except for U.K.)
ZD401	276 0632 907	Zener Diode MTZ.27D	
ZD451	276 0634 905	Zener Diode MTZ.3A	Europe Model Only (Except for U.K.)
ZD452	276 0633 906	Zener Diode MTZ.3.6C	
ZD471	276 0635 904	Zener Diode MTZ.7.5C	Europe Model Only (Except for U.K.)
SC471	279 0016 904	Thyristor SF0R1A42	
RESISTORS GROUP			
△ P207,208	244 2052 931	Metallic 3900hm 1W	RS14B3A391J.NBS(S)
△ P255,266	241 2387 940	Carbon 4.7ohm 1/4W	RD14B2E47J.NBS
△ R311,312	241 2379 932	Carbon 620ohm 1/4W	RD14B2E62J.NBS
△ R329,330	241 2379 962	Carbon 220ohm 1/4W	RD14B2E22J.NBS
△ R331-334	244 2043 982	Metallic 0.22ohm 1W	RS14B2A22J.NBS(S)
△ R343,344	241 2379 987	Carbon 1kohm 1/4W	RD14B2E10J.NBS
△ R345,346	241 2379 962	Carbon 330ohm 1/4W	RD14B2E33J.NBS

Ref. No.	Part No.	Part Name	Remarks
△ R385,386	241 2379 932	Carbon 620ohm 1/4W	RD14B2E21JNES
△ R387,389	241 2377 889	Carbon 150ohm 1/4W	RD14B2E21JNES
△ R393,394	244 2051 867	Metallic 47ohm 1/4W	RS14B3A47JNES(S)
△ R401	244 2051 867	Metallic 47ohm 1/4W	RS14B3A47JNES(S)
△ R408	241 2387 908	Carbon 10ohm 1/4W	RD14B2E21JNES
△ R411	241 2377 947	Carbon 10ohm 1/4W	RD14B2E21JNES
△ R471	244 2051 874	Metallic 10ohm 1/4W	RS14B3A10JNES(S)
△ R474	244 2051 990	Metallic 47ohm 1/4W	RS14B3A47JNES(S)
VR102	211 0831 002	Variable 100kohm	V1620V25F=104R(MG)
VR201	211 0830 003	Variable 100kohm	V14V20F104K
VR251	211 0827 003	Variable 250kohm	V11V20F254K
VR301	211 0828 002	Variable 250kohm	V14V20F254K
VR303	211 0829 001	Variable 50kohm	V14V20F503K
VR305,306	211 6083 912	Semi Fixed Resistor 4.7Kohm	V06PB472

CAPACITORS GROUP

C101,102	253 1179 945	Ceramic 220pF50V	CK45B1H221K
C103,104	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C105,106	254 4254 925	Electrolytic 33µF16V	CE04W1C330M
C107,108	253 4537 966	Ceramic 47pF50V	CC45SL1H470J
C109,110	255 1264 995	Film 5600pF50V	CQ93M1H562J(B)
C111,112	255 1264 994	Film 1500pF50V	CQ93M1H152J(B)
C113,114	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C115,116	253 1181 917	Ceramic 0.022µF50V	CK45F1H223Z
C121-124	253 4537 982	Ceramic 56pF50V	CC45SL1H560J
C127,128	253 4537 982	Ceramic 56pF50V	CC45SL1H560J
C129	253 1181 917	Ceramic 0.022µF50V	CK45F1H223Z
C131	253 1181 917	Ceramic 0.022µF50V	CK45F1H223Z
C133	253 1181 917	Ceramic 0.022µF50V	CK45F1H223Z
C135	253 1181 917	Ceramic 0.022µF50V	CK45F1H223Z
C136	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C141,142	255 1264 908	Film 1000pF50V	CQ93M1H102J(B)
C151	253 1146 907	Ceramic 0.01µF50V	CK45F1H103Z
C201-204	255 1264 982	Film 2200pF50V	CQ93M1H472J(B)
C213,214	255 1265 978	Film 0.022µF50V	CQ93M1H223J(B)
C215,216	253 1179 903	Ceramic 560pF50V	CK45B1H561K
C217	253 1181 917	Ceramic 0.022µF50V	CK45F1H223Z
C218,219	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C220	254 4252 927	Electrolytic 47µF10V	CE04W1A470M
C221	245 4260 948	Electrolytic 1µF50V	CE04W1H101M
C225,226	253 1148 907	Ceramic 0.01µF50V	CK45F1H103Z
C251	254 4256 952	Electrolytic 220µF25V	CE04W1E221M
C252-254	254 4258 918	Electrolytic 10µF35V	CE04W1V100M
C301,302	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C303,304	254 4260 922	Electrolytic 0.33µF50V	CE04W1HR33M
C305,306	253 1179 903	Ceramic 100pF50V	CK45B1H101K
C307,308	253 4537 982	Ceramic 56pF50V	CC45SL1H560J
C311-316	253 4536 909	Ceramic 100pF50V	CC45SL1H100D
C322,324	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C325,326	255 1265 978	Film 0.022µF50V	CQ93M1H223J(B)
C327-330	254 4262 904	Electrolytic 4.7µF63V	CE04W1A477M
C333,334	254 4254 925	Electrolytic 33µF16V	CE04W1C330M
C335,336	253 1179 903	Ceramic 100pF50V	CK45B1H101K
C337,338	255 1265 981	Film 0.027µF50V	CQ93M1H273J(B)
C339,340	256 1034 982	Film 0.12µF50V	CF93A1H124J
C341,342	255 1264 924	Film 1500pF50V	CQ93M1H152J(B)
C343,344	255 1265 936	Film 0.01µF50V	CQ93M1H103J(B)
C345,346	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C347	255 1265 936	Film 0.01µF50V	CQ93M1H103J(B)
C348	254 4263 945	Electrolytic 1µF100V	CE04W2A010M
C353,354	256 1034 979	Film 0.1µF50V	CF93A1H104J
C371-374	256 1034 979	Film 0.1µF50V	CF93A1H104J

Ref. No.	Part No.	Part Name	Remarks
C377,378	245 4260 948	Electrolytic 1µF50V	CE04W1H101M
C401	259 0007 702	For Back up 8200µF	SB CAP=822-C
C402	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C403	254 4256 790	Electrolytic 2200µF25V	CE04W1E222M
C404	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C406,407	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
△ C406,409	253 1181 905	Ceramic 470µF6.3V	CK45F1H472P
C415,416	254 4355 002	Electrolytic 6800µF50V	CE04W1H682MDL
C418	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
△ C419	256 1042 903	Film 0.1µF250V	CF93A204K
C451	254 4258 905	Electrolytic 4.7µF35V	CE04W1V477M
C452	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C458	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C471	254 4260 980	Electrolytic 10µF50V	CE04W1H100M
C472	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C473	254 4250 945	Electrolytic 330µF6.3V	CE04WQJ331M
C480	253 1146 907	Ceramic 0.01µF50V	CK45F1H103Z
C601,602	253 3131 907	Ceramic 27pF50V	CC45CH1H270J
C603-605	254 4250 916	Electrolytic 470µF6.3V	CE04WQJ470M
C607,608	253 4537 911	Ceramic 30pF50V	CC45SL1H300J
C609	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C610	254 4250 916	Electrolytic 470µF6.3V	CE04WQJ470M
C611	253 1179 990	Ceramic 560pF50V	CK45B1H561K

OTHERS PARTS GROUP

L101,102	235 9003 002	FTZ Choke Coil	
L391,392	235 0068 004	Inductor	1µH
RL471	214 0167 005	Relay	GS2-2A
XL601	399 0178 007	Crystal	4.332MHz
XL602	399 0041 901	Ceramic Filter	CSA4.00MG
	204 8354 004	Head Phone Jack	
	212 4778 009	2P Push Switch	SP, A-B
	205 0190 036	3P NH Connector base	TEST POINT
	204 8466 002	4P Pin Jack(S-GND)	
	204 8467 001	6P Pin Jack(S-GND)	
	205 0484 001	8P SP Terminal	Europe Model
	205 0472 015	8P SP Terminal	U.K. Model
CN2A	002 0012 065	2C Ribbon Cable	
CN3B	205 0343 032	3P Connector Base	
CN5A	002 0041 010	5C Ribbon Cable	
CN7A	205 0696 077	J.L. Connector(BT-E)	
CN8A	205 0535 002	8P Connector Base	
CN9B	205 0696 093	J.L. Connector(BT-E)	
CN9B	205 0748 093	9P J.L. Connector(R)	
CN27A	205 0880 016	27P FFC Connector Base	
	203 0539 060	1P SIN Cord Ass'y	
	203 0539 073	1P SIN Cord Ass'y	
	203 0539 086	1P SIN Cord Ass'y	
	203 0539 099	1P SIN Cord Ass'y	
	203 0475 043	1P Contact Ass'y	
	205 0185 025	2P Wire Holder	
	205 0185 054	5P Wire Holder	
	415 0309 013	P.V.C. Tube(L=10)	

1U-2732 TUNER UNIT (DRA365RD)

Ref. No.	Part No.	Part Name	Remarks
SEMICONDUCTORS GROUP			
IC501	263 0891 001	IC LA1265(S)	
IC502	263 0439 007	IC LA3401	
IC503	262 0719 009	IC LM7001	
IC504	263 0801 004	IC NUM7812FA(S)	
IC601	263 2039 017	IC TMP67CM71F-6192	
TR501	275 0051 909	Transistor 2SK161(GR)	
TR502	273 0434 902	Transistor 2SC2058S(Q)	
TR503	269 0150 902	Transistor DTB123ES	
TR504	273 0435 901	Transistor 2SC1740SLN(E)	
TR505	275 0053 907	Transistor 2SK365(BLGR)	
TR506	269 0046 906	Transistor DTA114ES(10K-10K)	
TR507,508	269 0040 902	Transistor DTC144ES(47K-47K)	
TR509	271 0279 909	Transistor 2SA1515(R)	
ZD501	276 0636 903	Zener Diode MTZJ6.2B	
ZD651	276 0636 903	Zener Diode MTZJ6.2B	

RESISTORS GROUP (Not included Carbon Film ±5% 1/4W)

Ref. No.	Part No.	Part Name	Remarks
CAPACITORS GROUP			
△ C419	256 1042 903	Ceramic 0.01µF250V	CK45F1H472P
C501-506	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C507	253 4536 954	Ceramic 16pF50V	CC45SL1H160J
C508	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C509	253 1179 903	Ceramic 100pF50V	CK45B1H101K
C510-513	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C514	254 4256 936	Electrolytic 47µF25V	CE04W1E470M
C515	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C516	254 4260 964	Electrolytic 3.3µF50V	CE04W1H333M
C517	253 1181 917	Ceramic 0.022µF50V	CK45F1H223Z
C518	254 4260 922	Electrolytic 0.33µF50V	CE04W1HR33M
C519	253 1179 903	Ceramic 100pF50V	CK45B1H101K
C520	256 1034 937	Film 0.047µF50V	CF93A1H473J
C521	253 9031 904	Ceramic 0.047µF25V	CK45F1E473K
C522,523	254 4254 912	Electrolytic 22µF16V	CE04W1C220M
C525	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C526,527	253 4448 903	Ceramic 330pF50V	CC45SL1H331J
C529	254 4254 938	Electrolytic 47µF16V	CE04W1C470M
C530	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C531	254 4260 919	Electrolytic 0.22µF50V	CE04W1HR22M
C532	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C533	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C534,535	254 4260 951	Electrolytic 2.2µF50V	CE04W1HR22M
C536	253 1146 907	Ceramic 0.01µF50V	CK45F1H103Z
C537	254 4260 906	Electrolytic 0.01µF50V	CE04W1HR01M
C538	254 4254 938	Electrolytic 47µF16V	CE04W1C470M
C539	254 3056 917	Electrolytic 1µF50V	CE04D1H010MBP
C540	253 1181 917	Ceramic 0.022µF50V	CK45F1H223Z
C542,543	253 4536 954	Ceramic 16pF50V	CC45SL1H160J
C544	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z
C545	254 4260 948	Electrolytic 1µF50V	CE04W1H101M
C546	254 4254 938	Electrolytic 47µF16V	CE04W1C470M
C547	254 4254 909	Electrolytic 10µF16V	CE04W1C100M
C548	254 4260 980	Electrolytic 10µF50V	CE04W1H100M
C551-554	253 1146 907	Ceramic 0.01µF50V	CK45F1H103Z
C651	255 1265 949	Film 0.012µF50V	CQ93M1H123J(B)
C652	254 4300 963	Electrolytic 100µF6.3V	CE04WQJ101M
C653	253 1181 904	Ceramic 0.01µF50V	CK45F1H103Z

Ref. No.	Part No.	Part Name	Remarks
OTHERS PARTS GROUP			
CF501,502	261 0064 007	Ceramic Filter	SFT10.7MS2
CF503	261 0116 007	Ceramic Filter	SFU450B3
CF504	261 0101 009	Ceramic Filter	SFU450C4N
△ F401	206 1016 016	Fuse 1.25A	
△ F402	206 1016 029	Fuse 1A	Europe Model Only (Except for U.K.)
RM501	499 0150 006	Remote Sensor	SBX1510-52
△ SW401	212303000	Power Switch	TV-5
SW501-503	212 5604 910	Tact Switch	
SW405-615	212 5604 910	Tact Switch	
T501	231 1913 004	MW Antenna Oscillator Coil	
T502	231 2098 009	FM IF DET Trans	
T503	231 1144 006	AM IFT	
T504	232 9010 009	Anti-birdie Filter	
T505,506	232 0085 004	LPF	
XL502	261 0103 007	Ceramic Oscillator	CBS456F11
XL503	399 0075 003	Crystal	7.2MHz
XL601	399 0191 903	Ceramic Oscillator	CST4.00MGW-TF01
	216 0065 006	Front End	
	363 4155 002	F.L.D.	
	205 0874 004	3P Antenna Terminal	FP14AM7R
	205 0624 007	2P AC Connector Base	PAL/F
CN3B	203 2361 003	2P SAN-3P PH Connector Cord	
CN3E	205 0581 056	2P VH Connector Base	
CN3D	205 0581 001	2P VH Connector Base	Europe Model Only (Except for U.K.)
CN7A	205 0748 077	J.L. Connector(R)	
CN8A	205 0536 001	8P Connector Socket	
CN27A	205 0880 016	27P FFC Connector Base	
△	203 0548 051	1P Contact Ass'y	
△	203 0548 064	1P Contact Ass'y	
△	203 0516 009	3P VH Connector Cord	Europe Model Only (Except for U.K.)
△	202 0040 909	Fuse Clip	

PRINTED WIRING BOARD PATTERNS

1

2

3

4





5

6

7

8

1U-2731B MAIN UNIT (DRA-565RD)



※

CN3F	} Europe Model Only (Except For U.K.)
TR402	
TR403	
C405	
R402	
R403	
R406	
R407	

1

1

10

1

1

1 2 3 4 5 6 7 8

1U-2731 MAIN UNIT (DRA-365RD)





A


B

C

D

E










1U-2732 TUNER & DISPLAY UNIT (DRA-365RD)


※ F402 } Europe Model Only
AC OUTLET } (Except For U.K.)

A
B
C
D
E



WIRING DIAGRAM

DRA-565RD




5

6


7

8

DRA-365RD



EXPLODED VIEW OF CHASSIS AND CABINET



PARTS LIST EXPLODED VIEW (DRA-565RD)


Ref. No.	Part No.	Part Name	Remarks	Q'ty	Ref. No.	Part No.	Part Name	Remarks	Q'ty
1	1U-2731 B	MAIN UNIT ASSY		1	48	102 0520 129	TOP COVER		1
1-1	—	MAIN UNIT			49	461 0769 009	RUBBER SHEET		2
1-2	—	VOLUME UNIT			50	122 0146 015	HIMERON SHEET		1
1-3	—	HEAD PHONE UNIT			51	445 0048 003	CORD HOLDER (L=75)		2
1-4	—	TRANS WIRE UNIT			52	009 0112 005	Z7P FFC CORD		1
2	1U-2732 B	TUNER/DISPLAY UNIT ASSY		1	53	254 4374 708	ELECTROLYTIC 8200 μ F56V		1
2-1	—	TUNER UNIT			54	412 2965 107	SIDE BRACKET		1
2-2	—	DISPLAY UNIT			SCREWS				
2-3	—	POWER UNIT			101	473 7015 018	TAPING SCREW 3x8 (S)	Black	4
2-5	—	POWER SW UNIT			102	473 7002 018	TAPING SCREW 3x8 (S)		10
2-6	—	TRANS PRE WIRE UNIT			103	473 8007 009	CUP SCREW 3x12		4
5	204 8354 004	HEAD PHONE JACK		1	104	473 7501 001	TAPING SCREW 3x10 (P)		3
6	214 9003 005	RELAY	RL471	1	105	477 0064 107	FOCUS SCREW 3x10	Black	12
7	211 0827 003	VARIABLE	VR251	2	106	473 7004 016	TAPING SCREW 4x8 (S)		4
8	211 0828 002	VARIABLE	VR301	1	107	473 7508 017	TAPING SCREW 3x10 (P)	Black	14
9	211 0829 001	VARIABLE	VR203	1	108	477 0263 005	3P SWELLING SCREW		4
10	211 0830 003	VARIABLE	VR201	1	109	473 7002 005	TAPING SCREW 3x8 (S)		9
11	211 0831 002	VARIABLE	VR102	1	PACKING AND ACCESSORIES (not included EXPLODED view)				
12	204 8466 002	4 PIN JACK		1	505 8125 009	POLY COVER			1
13	204 8467 001	6P PIN JACK		2	511 2837 007	OPERATING INSTRUCTION			1
14	212 4778 009	2P PUSH SWITCH		1	231 1914 003	AM LOOP ANTENNA			1
15	212 1074 007	1P PUSH SWITCH	SW901-615	1	395 0023 008	FM ANTENNA ASSY			1
16	212 5604 910	TACT SWITCH		15	399 0242 001	REMOTE CONTROL UNIT	RC-174		1
17	393 4155 002	FLD	RP14AM7R	1	505 0131 050	CABINET COVER			1
18	499 0150 008	REMOTE SENSOR	SBX1610-52	1	504 0125 005	STYRENE PAPER	For AC CORD		1
19	216 0065 006	FRONT END		1	503 1140 002	CUSHION			2
20	205 7015 029	FUSE 1A	F402 (Europe Model Only (Except for U.K.))	1	502 0741 956	PAD	U.K. Model Only		1
21	205 0647 004	3P ANTENNA TERMINAL		1	501 1783 010	CARTON CASE	Europe Model		1
22	203 2842 007	AC OUTLET	(Except for U.K.)	1	501 1783 023	CARTON CASE	U.K. Model		1
23	214 0176 009	RELAY(GSP-1)	RL401 (Europe Model (Except for U.K.))	1					
24	212 1030 009	POWER SWITCH(10V5)		1					
25	206 1015 081	FUSE 2A	F401 (Europe Model Only (Except for U.K.))	1					
26	205 0484 001	8P SPEAKER TERMINAL	Europe Model	1					
27	205 0472 013	8P SPEAKER TERMINAL	U.K. Model	1					
28	461 0539 022	RUBBER SHEET		1					
29	411 1285 006	MAIN CHASSIS		1					
30	105 1136 029	REAR PANEL	Europe Model	1					
31	105 1136 032	REAR PANEL	U.K. Model	1					
32	104 0194 106	FOOT ASSY		4					
33	417 0498 205	POWER RADIATOR		1					
34	273 0389 002	TRANSISTOR	TR321,322	2					
35	271 0240 006	TRANSISTOR	TR323,324	2					
36	415 0234 007	INSULATING SHEET		4					
37	412 3767 006	P.W.B. BRACKET		2					
38	206 2091 000	AC CORD WITH CONNECTOR	Europe Model	1					
39	206 2109 002	AC CORD WITH CONNECTOR	U.K. Model	1					
40	445 0056 008	CORD BUSH		1					
41	223 6116 006	POWER TRANS		1					
42	146 1495 127	INNER PANEL		1					
43	143 0880 006	WINDOW		1					
44	113 1679 008	BUTTON(4KEY)		2					
45	113 1680 107	BUTTON(7KEY)		1					
46	113 1558 006	PUSH BUTTON(KAKU)		3					
47	144 2370 119	FRONT PANEL		1					
48	112 0647 009	VOLUME KNOB		1					
49	112 0739 001	KNOB(MARU)		4					
50	113 9213 000	POWER BUTTON ASSY		1					

PARTS LIST EXPLODED VIEW (DRA-365RD)


Ref. No.	Part No.	Part Name	Remarks	Q'ty	Ref. No.	Part No.	Part Name	Remarks	Q'ty
1	1U-2731	MAIN UNIT ASSY		1	50	122 0146 015	HIMERON SHEET		1
1-1	---	MAIN UNIT			51	445 0048 003	CORD HOLDER (L=76)		1
1-2	---	VOLUME UNIT			52	009 0112 005	27P PFC CORD		1
1-3	---	HEAD PHONE UNIT			53	254 4355 002	ELECTROLYTIC 6800 μ F/50V		2
1-4	---	TRANS WIRE 1 UNIT			54	412 2855 107	SIDE BRACKET		1
2	1U-2732	TUNER/DISPLAY UNIT ASSY		1	SCREWS				
2-1	---	TUNER UNIT			101	473 7015 018	TAPING SCREW 3x8 (S)	Black	4
2-2	---	DISPLAY UNIT			102	473 7002 018	TAPING SCREW 3x8 (S)		10
2-3	---	POWER UNIT			103	473 8007 009	CUP SCREW 3x12		4
2-5	---	POWER SW UNIT			104	473 7501 001	TAPING SCREW 3x10 (P)		2
2-6	---	TRANS PRE WIRE UNIT			105	477 0064 107	FIXING SCREW 3x10	Black	10
5	204 8254 004	HEAD PHONE JACK		1	106	473 7004 016	TAPING SCREW 4x8 (S)		4
6	214 9003 005	RELAY	FL471	1	107	473 7506 017	TAPING SCREW 3x10 (P)	Black	14
7	211 0627 003	VARIABLE <i>Vor. Loud.</i>	VR251	2	108	477 0263 005	3P SWELLING SCREW		4
8	211 0628 002	VARIABLE <i>Bass</i>	VR301	1	109	473 7002 005	TAPING SCREW 3x8 (S)		9
9	211 0629 001	VARIABLE <i>Treble</i>	VR303	1	PACKING AND ACCESSORIES (not included EXPLODED view)				
10	211 0630 003	VARIABLE <i>Balance</i>	VR201	1	505 9125 009	POLY COVER			1
11	211 0631 002	VARIABLE <i>Volume</i>	VR102	1	511 2637 007	OPERATING INSTRUCTION			1
12	204 8466 002	4P PIN JACK		1	231 1914 003	AM LOOP ANTENNA			1
13	204 8467 001	6P PIN JACK		2	395 0023 008	FM ANTENNA ASSY			1
14	212 4778 009	2P PUSH SWITCH		1	399 0242 001	REMOTE CONTROL UNIT	RC-174		1
15	---	---		1	505 0131 050	CABINET COVER			1
16	212 5804 910	TACT SWITCH		14	504 0125 005	STYRENE PAPER	For AC CORD		1
17	393 4155 002	FLD	FP14AM7R	1	503 0939 007	CUSHION			2
18	499 0150 008	REMOTE SENSOR	SBX1610-52	1	502 0741 056	PAD	U.K. Model Only		1
19	216 0065 006	FRONT END		1	501 1782 011	CARTON CASE	Europe Model		1
20	206 3015 025	FUSE 1A	F402	1	501 1782 024	CARTON CASE	U.K. Model		1
21	205 0647 004	3P ANTENNA TERMINAL	Europe Model Only (Except for U.K.)	1					
22	203 8942 007	AC OUTLET	Europe Model Only (Except for U.K.)	1					
23	---	---		1					
24	212 3030 009	POWER SWITCH (TV-5)		1					
25	206 3015 016	FUSE 1.25A	F401	1					
26	205 0484 001	8P SPEAKER TERMINAL	Europe Model	1					
27	205 0472 019	8P SPEAKER TERMINAL	U.K. Model	1					
28	461 0536 022	RUBBER SHEET		1					
29	411 1285 006	MAIN CHASSIS		1					
30	105 1135 020	REAR PANEL	Europe Model	1					
31	105 1136 033	REAR PANEL	U.K. Model	1					
32	104 0194 106	FOOT ASSY		4					
33	417 0498 216	POWER RADIATOR		1					
34	273 0396 005	TRANSISTOR	TR321,322	2					
35	271 0237 006	TRANSISTOR	TR323,324	2					
36	415 0234 007	INSULATING SHEET		4					
37	412 3767 006	P.W.B. BRACKET		2					
38	206 2091 000	AC CORD WITH CONNECTOR	Europe Model	1					
39	206 2109 002	AC CORD WITH CONNECTOR	U.K. Model	1					
40	445 0056 006	CORD BUSH		1					
41	233 6115 007	POWER TRANS		1					
42	146 1493 129	INNER PANEL		1					
43	143 0680 006	WINDOW		1					
44	113 1679 006	BUTTON(4KEY)		2					
45	113 1680 110	BUTTON(6KEY)		1					
46	---	---		3					
47	144 2369 010	FRONT PANEL		1					
48	112 0647 009	VOLUME KNOB		1					
49	112 0739 001	KNOB(MARU)		4					
50	113 9213 000	POWER BUTTON ASSY		1					
51	102 0426 223	TOP COVER		1					
52	461 0769 009	RUBBER SHEET		2					


EXPLODED VIEW OF CHASSIS AND CABINET

DRA-365RD



SCHEMATIC DIAGRAM (for DRA-565RD)




WARNING:
Parts marked with this symbol  have critical characteristics. Use ONLY replacement parts recommended by the manufacturer.

CAUTION:
Before returning the unit to the customer, make sure you make either (leakage current exceeds 0.5 milliamps, or if the resistance from chassis

WARNING:
DO NOT return the unit to the customer until the problem is located and

NOTES:
Circuit and parts are subject to change without prior notice.




or (1) a leakage current check or (2) a line to chassis resistance check. If the ss is to either side of the power cord is less than 240 kohms, the unit is defective.

and corrected.

NOTES


ALL RESISTANCE VALUES IN OHM. K=1,000 OHM, M=1,000,000 OHM
ALL CAPACITANCE VALUES IN MICRO FARAD. P=MICRO-MICRO FARAD
EACH VOLTAGE AND CURRENT ARE MEASURED AT NO SIGNAL INPUT CONDITION.
CIRCUIT AND PARTS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

SCHEMATIC DIAGRAM (for DRA-365RD)



NOTES


ALL RESISTANCE VALUES IN OHM. K=1,000 OHM, M=1,000,000 OHM
 ALL CAPACITANCE VALUES IN MICRO FARAD. P=MICRO-MICRO FARAD
 EACH VOLTAGE AND CURRENT ARE MEASURED AT NO SIGNAL INPUT CONDITION.
 CIRCUIT AND PARTS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

WARNING:
 Parts marked with this symbol  have critical ch
 Use ONLY replacement parts recommended by the mar

CAUTION:
 Before returning the unit to the customer, make sure you
 leakage current exceeds 0.5 milliamperes, or if the resistan

WARNING:
 DO NOT return the unit to the customer until the problem

NOTES:
 Circuit and parts are subject to change without pr



tical characteristics.
18 manufacturer.

re you make either (1) a leakage current check or (2) a line to chassis resistance check. If the
istance from chassis to either side of the power cord is less than 240 kohms, the unit is defective.

problem is located and corrected.

out prior notice.